



YOUTH 170 UTV PRODUCTION

Limited Youth 170 UTV

** Updated February 22nd, 2022 **

DEFINITION

Polaris RZR 170 or Polaris ACE 150. Driver must be at least five (5) years old. Maximum age is twelve (12) years old.

GENERAL REGULATIONS

Entrants in this class shall comply with all applicable general regulations.

TECHNICAL REGULATIONS

This class is a stock production class, and all components must remain stock except for those modifications allowed herein.

***NOTE:** The UTR abbreviations listed under this class (I.E. UTR1 HELMETS) refer to UTR cross reference listings in the front of this book. These UTR cross-referenced listings are part of the class rules. Where a conflict occurs between the UTR cross-referenced listing and a rule contained under this class, the rule contained under this class takes priority.*

SAFETY EQUIPMENT

UTR1 HELMETS

UTR2 PROTECTIVE CLOTHING

SFI-A5 rated fire suit is required. No karting suits.

UTR3 EYE PROTECTION and DENTURES

UTR4 HEAD AND NECK RESTRAINTS

SUSPENSION COMPONENTS

Stock suspension points must be retained.

A-arms and rear trailing arms are open.

Maximum front and rear track width is 53.5 inches outside of tire to outside of tire at dies height.

Maximum wheelbase is 68.5 inches measured at ride height.

Minimum ride height is 6 inches.

Stock spindles must be used.

Front and rear hubs may be of any manufacturer.

UTR11 SHOCK ABSORBERS and BUMP STOPS

Must retain stock shock mounting locations

UTR12 SECONDARY SUSPENSION
UTR13 WHEELS and TIRES
UTR14 FASTENERS

STEERING and BRAKE COMPONENTS

UTR15 STEERING

Tie rods are open.

UTR16 BRAKES

Front brakes may be removed. Brake caliper and disc are open. Mounting and location are open.

ELECTRICAL SYSTEM

UTR17 IGNITION

UTR18 BATTERIES

UTR20 STARTERS

FUEL SYSTEM

UTR21 FUEL

UTR22 FUEL TANKS

UTR23 FUEL FILLERS LINES, VENTS, and CAPS

ENGINE, TRANSMISSION and DRIVELINES

UTR24 ENGINE and ENGINE DISPLACEMENT

Polaris RZR 170cc engine or Polaris ACE 150 engine mandatory.

Engines must remain stock as delivered by the manufacturer.

Clutch is open.

ECU must remain stock.

Intake, exhaust, and fuel programmer allowed.

UTR25 ENGINE REPLACEMENT

UTR26 TRANSMISSION

Transmission case may be reinforced.

UTR27 THROTTLES

UTR28 EXHAUST

Open.

UTR29 DRIVE SHAFTS

Rear axle is open. Maximum width must be maintained.

UTR31 FLUID COOLERS**VEHICLE SAFETY EQUIPMENT****UTR34 ROLL CAGES**

Aftermarket roll cage required. No stock cages.

UTR35 SAFETY HARNESS**UTR36 SAFETY NETS****UTR37 SEATING**

Driver's seat must remain in stock location plus or minus two (2) inches.

GENERAL VEHICLE COMPONENTS**UTR38 DRIVERS COMPARTMENT****UTR39 DOORS AND LATCHES****UTR40 FIREWALLS****UTR41 BALLAST****UTR42 WEIGHT**

Minimum weight is 650 pounds, including driver.

UTR43 FLOORBOARDS**UTR44 BUMPERS and HAZARDOUS PROTRUSIONS****UTR45 MIRRORS****UTR46 SKID PLATES****UTR47 STORAGE****UTR48 CHASSIS and BODY**

Roof panel required. Must be minimum of .060 thick metal.

UTR49 HOSES**UTR50 IDENTIFICATION MARKINGS**

Race numbers required on both sides and rear of vehicle. black numbers on a white background only. Minimum six (6) inch tall numbers.

M400 will assign race numbers.

UTR51 ADVERTISING on VEHICLES**UTR52 RADIO EQUIPMENT****UTR53 WORKMANSHIP****UTR54 TRACKING DEVICE**