



# YOUTH 200 UTV PRODUCTION

## Limited Youth 200 UTV

*\* Updated January 28th, 2022 \**

### DEFINITION

Polaris RZR 200. Driver must be at least five (5) years old. Maximum age is twelve (12) years old.

### GENERAL REGULATIONS

Entrants in this class shall comply with all applicable general regulations.

### TECHNICAL REGULATIONS

This class is a stock production class, and all components must remain stock except for those modifications allowed herein.

**NOTE:** The UTR abbreviations listed under this class (I.E. UTR1 HELMETS) refer to UTR cross reference listings in the front of this book. These UTR cross-referenced listings are part of the class rules. Where a conflict occurs between the UTR cross-referenced listing and a rule contained under this class, the rule contained under this class takes priority.

## SAFETY EQUIPMENT

### UTR1 HELMETS

### UTR2 PROTECTIVE CLOTHING

SFI-A5 rated fire suit is required. No karting suits.

### UTR3 EYE PROTECTION and DENTURES

### UTR4 HEAD AND NECK RESTRAINTS

## SUSPENSION COMPONENTS

Stock suspension points must be retained.

A-arms are open.

Maximum front and rear track width is 53.5 inches outside of tire to outside of tire at ride height.

Maximum wheelbase is 68.5 inches measured at ride height.

Minimum ride height is 6 inches.

Stock spindles must be used.

Front and rear hubs may be of any manufacturer.

### UTR11 SHOCK ABSORBERS and BUMP STOPS

Must retain stock shock mounting locations

**UTR12 SECONDARY SUSPENSION**

**UTR13 WHEELS and TIRES**

**UTR14 FASTENERS**

**STEERING and BRAKE COMPONENTS**

**UTR15 STEERING**

Tie rods are open.

**UTR16 BRAKES**

Front brakes may be removed. Rear caliper and disc are open. Mounting location optional.

**ELECTRICAL SYSTEM**

**UTR17 IGNITION**

**UTR18 BATTERIES**

**UTR20 STARTERS**

**FUEL SYSTEM**

**UTR21 FUEL**

**UTR22 FUEL TANKS**

**UTR23 FUEL FILLERS LINES, VENTS, and CAPS**

**ENGINE, TRANSMISSION and DRIVELINES**

**UTR24 ENGINE and ENGINE DISPLACEMENT**

Polaris RZR 200cc engine mandatory.

Engines must remain stock as delivered by the manufacturer.

Clutch must remain stock as delivered by the manufacturer.

ECU must remain stock.

Intake, exhaust, and fuel programmer allowed.

**UTR25 ENGINE REPLACEMENT**

**UTR26 TRANSMISSION**

Axle length is open.

**UTR27 THROTTLES**

**UTR28 EXHAUST**

Stock OEM exhaust is mandatory.

**UTR29 DRIVE SHAFTS**  
**UTR31 FLUID COOLERS**

## **VEHICLE SAFETY EQUIPMENT**

### **UTR34 ROLL CAGES**

Aftermarket roll cage required. No stock cages.

### **UTR35 SAFETY HARNESS**

### **UTR36 SAFETY NETS**

### **UTR37 SEATING**

Driver's seat must remain in stock location plus or minus two (2) inches.

## **GENERAL VEHICLE COMPONENTS**

### **UTR38 DRIVERS COMPARTMENT**

### **UTR39 DOORS AND LATCHES**

### **UTR40 FIREWALLS**

### **UTR41 BALLAST**

### **UTR42 WEIGHT**

Minimum weight is 800 pounds, including driver.

### **UTR43 FLOORBOARDS**

### **UTR44 BUMPERS and HAZARDOUS PROTRUSIONS**

### **UTR45 MIRRORS**

### **UTR46 SKID PLATES**

### **UTR47 STORAGE**

### **UTR48 CHASSIS and BODY**

Roof panel required. Must be minimum of .060 thick metal.

### **UTR49 HOSES**

### **UTR50 IDENTIFICATION MARKINGS**

Race numbers required on both sides and rear of vehicle. black numbers on a white background only. Minimum six(6) inch tall numbers.

M400 will assign race numbers.

### **UTR51 ADVERTISING on VEHICLES**

### **UTR52 RADIO EQUIPMENT**

### **UTR53 WORKMANSHIP**

### **UTR54 TRACKING DEVICE**