



YOUTH 570 OPEN UTV

Open Youth 570cc UTV

** Updated February 18th, 2021 **

DEFINITION

Two seat vehicles built using a production UTV. Any manufacture UTV may be used providing the model used has been series produced in a minimum of 1000 units within a twelve (12) month period. Maximum engine size 600cc. Stock production body parts required. Driver must be ten (10) years old minimum. Maximum age is sixteen (16) years old.

GENERAL REGULATIONS

Entrants in this class shall comply with all applicable general regulations.

TECHNICAL REGULATIONS

This class is an Open class, and all components will be considered open unless unrestricted herein. Manufactures body, engine, transmission, chassis, and drive train components must be retained.

***NOTE:** The UTR abbreviations listed under this class (I.E. UTR1 HELMETS) refer to UTR cross reference listings in the front of this book. These UTR cross-referenced listings are part of the class rules. Where a conflict occurs between the UTR cross-referenced listing and a rule contained under this class, the rule contained under this class takes priority.*

SAFETY EQUIPMENT

UTR1 HELMETS

UTR2 PROTECTIVE CLOTHING

UTR3 EYE PROTECTION and DENTURES

UTR4 HEAD AND NECK RESTRAINTS

UTR5 FIRST AID KIT

UTR6 EMERGENCY SIGNALING DEVICES

UTR7 HORNS

UTR8 REFLECTORS

UTR9 FIRE SUPPRESSION EQUIPMENT

UTR10 SURVIVAL SUPPLIES

SUSPENSION COMPONENTS

UTR11 SHOCK ABSORBERS and BUMP STOPS

Shocks are open.

UTR12 SECONDARY SUSPENSION

UTR13 WHEELS and TIRES

UTR14 FASTENERS

STEERING and BRAKE COMPONENTS

UTR15 STEERING

UTR16 BRAKES

ELECTRICAL SYSTEM

UTR17 IGNITION

UTR18 BATTERIES

UTR19 LIGHTS

UTR20 STARTERS

FUEL SYSTEM

UTR21 FUEL

UTR22 FUEL TANKS

UTR23 FUEL FILLERS LINES, VENTS, and CAPS

ENGINE, TRANSMISSION and DRIVELINES

UTR24 ENGINE and ENGINE DISPLACEMENT

Maximum engine displacement is 600cc.

Engine must remain stock as delivered by the manufacture.

No engine parts may be modified or replaced.

UTR25 ENGINE REPLACEMENT

UTR26 TRANSMISSION

UTR27 THROTTLES

UTR28 EXHAUST

Open.

UTR29 DRIVE SHAFTS

UTR30 FLYWHEEL SHIELDS

UTR31 FLUID COOLERS

UTR32 AUXILIARY EQUIPMENT

UTR33 SUPERCHARGERS and TURBOCHARGERS

VEHICLE SAFETY EQUIPMENT

UTR34 ROLL CAGES

Stock production roll cages are not allowed.

UTR35 SAFETY HARNESS

UTR36 SAFETY NETS

UTR37 SEATING

GENERAL VEHICLE COMPONENTS

UTR38 DRIVERS COMPARTMENT

UTR39 DOORS AND LATCHES

Doors must be securely closed.

UTR40 FIREWALLS

UTR41 BALLAST

UTR42 WEIGHT

1200 pounds minimum weight, including the driver.

UTR43 FLOORBOARDS

UTR44 BUMPERS and HAZARDOUS PROTRUSIONS

Safe front and rear bumpers required. No sharp corners or hazardous protrusions.

UTR45 MIRRORS

UTR46 SKID PLATES

UTR47 STORAGE

UTR48 CHASSIS and BODY

Stock grill, hood, and front and rear fenders must be used.

Roof must be covered with sheet metal .060 thick minimum.

UTR49 HOSES

UTR50 IDENTIFICATION MARKINGS

Race numbers required on both sides and rear of vehicle. black numbers on a white background only. Minimum six(6) inch tall numbers.

M400 will assign race numbers.

UTR51 ADVERTISING on VEHICLES

UTR52 RADIO EQUIPMENT

UTR53 WORKMANSHIP

UTR54 TRACKING DEVICE